## Product data sheet Characteristics

# QOU215H

# QOU Miniature Circuit Breaker, 15A, 2P, 240V, 10kA

Product availability: Stock - Normally stocked in distribution facility







#### Main

TTT-CALL T		<u></u>
Product or component type	Miniature circuit-breaker	
Range of product	QOU	
Circuit breaker type	Standard	
Circuit breaker application	HACR and Switching Duty rated	JC 21

#### Complementary

Complementary		.≝
Line Rated Current	15 A	
Poles description	2P	В
Breaking capacity	5 kA at: 48 V DC 10 kA at: 240 V AC	determin
Electrical connection	Slotted box lugs, line side Slotted box lugs, load side	sed for
System Voltage	240 V AC 48 V DC	to to be
Mounting mode	Unit mount	<u>.</u>
AWG gauge	AWG 14AWG 2 (aluminium/copper)	
Height	4.05 in	
Depth	2.95 in	tsq.
Width	1.5 in	, and a second s
		70

#### Environment

		¥
Product certifications	IEC	<u>.</u>
1 Toddot och infoations		
	CSA	i i
	UL listed	<del>"</del>
	or noted	<u>u</u>

#### Ordering and shipping details

Category	00900 - QOU BREAKERS & SWITCH	<u>.</u> 2
		<u>_</u>

Discount Schedule	DE2
GTIN	00785901848462
Nbr. of units in pkg.	1
Package weight(Lbs)	0.72999999999998
Returnability	Y
Country of origin	MX

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1323 - Schneider Electric declaration of conformity
	Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold
	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

#### Contractual warranty

Warranty period	18 months