Product data sheet Characteristics

RC816F150C METER MAIN RINGLESS OH/UG 150A

Product availability: Stock - Normally stocked in distribution facility







Main

Product or component type	Meter Mains
Range of product	Homeline

Complementary

		•
Line Rated Current	150 A	
Short-circuit current	22 kA	
Meter socket type	Ringless	
Device mounting	Surface	<u>;</u>
Number of spaces	8	
Number of circuits	16	i
Product mounting	Surface	
Number of tandem circuit breakers	8	
Hub type	A	a
Electrical connection	Lugs line side Feed-thru lugs service ground	
AWG gauge	AWG 6350 kcmil (aluminium/copper) line side AWG 12AWG 2/0 (aluminium/copper) service ground	ئ مرد عامر ا
Device composition	Service disconnect (factory installed)	4
Service disconnect rated current	150 A	
Branch circuit breaker rated current	150 A	o o
Service feed location	OH UG	
Bypass type	No bypass	i o

Ordering and shipping details

00048 - HOM METER MAINS
DE3A
00785901859192

Nbr. of units in pkg.	1	
Package weight(Lbs)	42.5399999999999	
Returnability	Υ	
Country of origin	MX	

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 0944 - Schneider Electric declaration of conformity
	Schneider Electric declaration of conformity
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months