


T&B Conduit Fittings

Rigid and Intermediate Metal Conduit Fittings



Bushed Elbows




The noninsulated elbow has smoothly rounded shoulders to protect conductor insulation. Malleable iron.

Cat. No.	Size	Dimensions (in.)		
		A	B	C
460TB	1/2"	1-13/16	1-1/8	5/8
461TB	3/4"	2-1/4	1-1/2	9/16
462	1"	2-23/32	1-23/32	11/16
463	1-1/4"	3-1/8	2-1/16	25/32

For Dura-Plate™ finish, add prefix 040- to Cat. No. Consult Customer Service for details.

Short Elbows—Nylon Insulated




The integral insulation of the insulated elbow is a guarantee that the bushing of every fitting will be smooth. Malleable iron.

Cat. No.	Size	Dimensions (in.)		
		A	B	C
4290	1/2"	1-7/32	1-1/4	1/2
4291	3/4"	1-7/16	1-5/16	9/16
4292	1"	1-23/32	1-9/16	11/16
4293	1-1/4"	2-7/32	2-1/16	13/16
4294	1-1/2"	2-15/32	2-3/16	13/16
4295	2"	3	2-9/16	13/16

For Dura-Plate™ finish, add prefix 040- to Cat. No. Consult Customer Service for details. Not U.L. Listed

Short Elbows



When an insulated elbow is not desired, the Noninsulated short elbow should be used. Malleable iron.

Cat. No.	Size	Dimensions (in.)		
		A	B	C
4250	1/2"	1-5/16	1-1/4	7/16
4251	3/4"	1-17/32	1-5/16	1/2
4252	1"	1-13/16	1-9/16	5/8
4253	1-1/4"	2-9/32	2-1/16	11/16
4254	1-1/2"	2-9/16	2-3/16	11/16
4255	2"	3-3/32	2-9/16	11/16

For Dura-Plate™ finish, add prefix 040- to Cat. No. Consult Customer Service for details.