



BURNDY Catalog Number	YA44L2NT38FX
UPC Number	7818100214222
Description	CULUG-750FX-3/8X1-NARTNG
Status	Active

Web Use
BURNDY Product Line

Dimensional	
Tongue Angle	Straight
Length (in)	4.74
Tongue Type	Standard
Barrell Style	Chamfered
Bolt Hole Size (in)	0.39
Barrel Type	Standard
Thickness	0.33
B Length (in)	1.65
Pad Width (in)	1.63
E - in	1.00
Strip Length	1-5/8
General	
Number of Holes	2
Product Description	Copper Compression Lug, Narrow Tongue, 2 Hole w/ Inspection Window, 777.7 Flex, 3/8" Stud, 1" Stud Hole Spacing, Short Barrel, Tin - Electro Plated
Conductor(s)	
Flex (Class G) Size - Range	750
Flex (Class H) Size - Range	750
Flex (Class I) Size - Range	750
Copper Solid Size (Range)	N/A
DLO Size (Range)	777.7 (1925/#24)
Copper Stranded (Range)	750
Physical	
Type of Plating	Tin - Electro Plated
Bolt Hole Size	3/8
Color Code	Yellow
Plated (Yes or No)	Y
Index Number	L115
Product Material	Copper
Approvals / Certifications	
UL Listed	Y
CSA Certified	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N
Documentation	

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
Monday - Friday
Phone: 800-346-4175