# Product data sheet Characteristics

# 9070TF500D33 TRFMR CONTROL 500VA MULTIPLE VOLTAGES

Product availability: Stock - Normally stocked in distribution facility





Price\*: 957.00 USD



#### Main

Enclosure type	Open box
Range of product	TF

### Complementary

Depth	5.46 in	
Device composition	Top fuse disconnector	
Electrical connection	Screw clamp terminal	
Fuse type	0.41 x 1.50 in CC fuse mounting on top	i
Height	5.1 in	
Material	Copper winding	
Mounting support	Panel	a
Network number of phases	1 phase	
Primary voltage	380/400/415 V	.y
Rated power in VA	500 VA	
Secondary voltage	115/230 V	
Temperature rise	115 °C	ihstiit
Width	4.5 in	 ਹ
		T C

#### **Environment**

Insulation temperature	356 °F (180 °C)	
Product certifications	CSA file LR37055 guide 184-N-90	
	CE	
	UL listed file E61239	
Standards	NEC 450	-
	UL 508	F

## Ordering and shipping details

Category	16203 - 9070 TF (NOT T) 250-1000VA
Discount Schedule	CP8
GTIN	00785901314479
Nbr. of units in pkg.	1
Package weight(Lbs)	12.63000000000001
Returnability	Υ
Country of origin	MX

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1227 - Schneider Electric declaration of conformity
	Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold
	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

## Contractual warranty

Warranty period	18 months	