



PRODUCT DATA SHEET

Zinc-It® Instant Cold Galvanize™ Zinc Rich Galvanize Coating, 1 Gal

No. 18413 | Item# 1005242 | Case# 1005241



Product Description

High-performance coating of >92% pure zinc that electrochemically bonds with ferrous metals to form a galvanic cell. It actively fights rust and corrosion. Use as a touch-up for damaged galvanized coatings. Dries quickly. Outdoor protection: 1 - 2 years

Applications

On threads, exposed edges, fasteners, conduit, strapping, welds, fencing, railings, grates, electrical poles, breaker panel housings, rain spouts, signs, doors, trailers, waste containers, catwalks, and guard rails.

Unit Package Description

1 Gallon Can

Brand

CRC

Generic Description 1

Instant Cold Galvanized Coating

Net Fill

1 Gal

UPC Code

078254184135

Unit Dimensions

7.88H x 8W x 8D in

Units Per Case

1

Case Dimensions

9.8H x 9.4W x 9.1D in

Cases Per Pallet

60

Case Weight

22 lbs

I 2 of 5 Code

30078254184136

Appearance

Gray Viscous Liquid

Flash point (F)

45°F

Flash point (C)

7°C

Flammability Class - CPSC

Flammable

Spec Gravity Concentrate

2.47

Plastic Safe

May Harm Sensitive Plastics

Evaporation Rate

Slow

Dry Time - Fully Dry

72 Hours

Dry Time - Tack Free

30 Minutes

Last revised: 3/27/2018
Page 1 of 2



Customer Care: 800-556-5074
Technical Assistance: 800-521-3168
www.crcindustries.com

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.



PRODUCT DATA SHEET



Recoat	8 Hours
Coverage	674 Sq Ft at 1 Mil Dry
Working Temp (F)	250 to 300°F (Continuous), Up to 450°F (Intermittent)
Working Temp (C)	121.1 to 148.9°C (Continuous), 232.2°C (Intermittent)
Propellant	None
Military Specification Number	Meets requirements of Mil-P-26915, Meets requirements of Mil-P-46105
DOT Proper Shipping Name	Paint, Limited Quantity
VOC % (Consumer Product def)	19.95
VOC g/L (Consumer Product def)	493.36
VOC lbs/gal (Consumer Prod def)	4.11
VOC Category	Not Regulated - (Not for field application)
Removal (How To)	Paint stripper or other solvent

Last revised: 3/27/2018
Page 2 of 2



Customer Care: 800-556-5074
Technical Assistance: 800-521-3168
www.crcindustries.com

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.