# **T&B** Fittings

### **Conduit Bodies and Covers**

## **Conduit Outlet Bodies**

#### **Application**

Conduit Bodies are installed in conduit systems to:

- Connect conduit sections
- · Act as pull outlets when conductors are being installed
- Provide easy access for splices in branch conductors
- Make 90° bends in conduit runs
- Act as mounting outlets for wiring devices and lighting fixtures
- Provide access to conductors for maintenance and future system changes

#### **Features**

- Standard features include tapered (NPT) threads and integral bushings to protect wire insulation
- T&B Form 7 bodies and covers are interchangeable with other manufacturers' Form 7 bodies and covers
- T&B Form 8 bodies and covers are interchangeable with other manufacturers' Form 8 bodies and covers
- T&B Form 7 and Form 8 cast iron bodies feature BlueKote® internal coating for easier wire pulling
- T&B Series 35 bodies and covers are interchangeable with other manufacturers' 35/5 Series iron and steel bodies and covers
- Form 7 sand cast aluminum is made with a special aluminum alloy, providing superior corrosion resistance as cast; no protective coatings needed
- Special sand cast aluminum alloy makes these conduit bodies ideal for use in food and beverage, pharmaceutical, chemical processing and other corrosive environments
- All Form 7 and Form 8 covers include gaskets



#### **Materials**

Form 7, Form 8 and Series 35 Iron Conduit Bodies Sand-cast class 30 gray iron alloy
Stainless Steel Conduit BodiesType 316 stainless steel
Form 7 aluminumSand-cast CorroStall™ aluminum alloy
Covers Sand-cast gray iron alloy and stamped sheet steel with steel-stainless steel screws
Stainless Steel CoversCast and stamped Type 316 stainless steel with stainless steel screws
GasketsNeoprene
Aluminum CoversSand-cast CorroStall™ aluminum alloy or sheet aluminum with stainless steel screws, aluminum clips and stainless steel and Neoprene O-ring washer

#### **Finish**

Form 7, Form 8 and Series 35 Iron Conduit BodiesZinc-plating with aluminum acrylic coating
Form 7 and Form 8 Iron BodiesInternal PTFE-based BlueKote® coating
Covers
Aluminum Bodies and CoversAs cast

#### Listings/Compliances

UL Standard: 514A, 514B Fed. Spec: W-C-586D CSA Standard: C22.2 No. 18





United States
Tel: 901.252.8000
800.816.7809
Fax: 901.252.1354

Technical Services
Tel: 888.862.3289



## **Conduit Bodies and Covers**

	k Refer						HUB SIZ	Œ (IN.)				
	SHAPE	ТҮРЕ	1/2	3/4	1	11/4	11/2	2	<b>2</b> ½	3	31/2	4
		BlueKote® Form 7	LB17	LB27	LB37	LB47	LB57	LB67	LB77	LB87	LB97	LB107
		BlueKote® Form 8*	LB18	LB28	LB38	LB448	LB58	LB68	LB78	LB888	LB98	LB108
G 114120	LB	Series 35	LB50M	LB75M-TB			LB150M		LB250M	LB300M		LB400M
CSP CSP AND A CO		Sand Cast Aluminum Form 7	LB17SA	LB27SA	LB37SA	LB47SA	LB57SA	LB67SA	LB77SA	LB87SA	LB97SA	LB107SA
		Stainless Steel Form 8	LB18SST	LB28SST	LB38SST	LB48SST	LB58SST	LB68SST	(with o	covers, ga	skets and scr	ews)
		BlueKote® Form 7	LU17	LU27	LU37	LU47	LU57	LU67	_	_	_	_
	LU	Stainless Steel Form 8	LU18SST	LU28SST	LU38SST	LU48SST	LU58SST	LU68SST	(with o	covers, ga	skets and scr	ews)
		Sand Cast Aluminum Form 7	LU17SA	LU27SA	LU37SA	LU47SA	LU57SA	LU67SA	_	_	_	_
		BlueKote® Form 7	T17	T27	T37	T47	T57	T67	T77	T87	T97	T107
		BlueKote® Form 8*	T18	T28	T38-TB	T448	T58	T68	T78	T88-TB	_	_
		Series 35	T50M	T75M	T100M	T125M	T150M	T200M	T250M	T300M	T350M	T400M
100		Sand Cast Aluminum Form 7	T17SA	T27SA	T37SA	T47SA	T57SA	T67SA	T77SA	T87SA	T97SA	T107SA
		Stainless Steel Form 8	T18SST	T28SST	T38SST	T48SST	T58SST	T68SST			skets and scr	
		BlueKote® Form 7	C17	C27	C37	C47	C57	C67	C77-TB	C87		
-		BlueKote® Form 8*	C18	C28	C38	C448	C58-TB	C68	C78	C88	_	_
G TRA 1/2"	C	Series 35	C50M	C75M-TB	C100M	C125M	C150M		C250M-TB		C350M	C400M
		Sand Cast Aluminum Form 7	C17SA	C27SA	C37SA	C47SA	C57SA	C67SA	0ZJUW-1D	COUNT	OSSOIVI	OHOOM
		BlueKote® Form 7	LL17	LL27	LL37	LL47	LL57	LL67	 LL77	 LL87	LL97	LL107
l		BlueKote® Form 8*	LL17	LL28	LL37	LL448	LL57 LL58	LL68	LL78	LL888	LLJI	LLIUI
		Series 35	LL50M	LL75M	LL100M	LL125M	LL150M	LL200M	LL250M	LL300M	LL350M	LL400M
		Sand Cast Aluminum Form 7	LL17SA	LL27SA	LL37SA	LL47SA	LL57SA	LL67SA		LLJUUIVI	LLJJUIVI	LL400W
			LR17	LR27	LR37	LR47	LR57	LR67	 LR77	 LR87	LR97	LR107
3	BlueKote® Form 8		LR17 LR18	LR28	LR38	LR448	LR58	LR68	LR78	LR888	Ln9/	LNIUI
	LR	Series 35		LR75M		LR125M					L DOEOM TD	
			LR50M		LR100M		LR150M	LR200M	LR250M		LR350M-TB	LK400W
		Sand Cast Aluminum Form 7	LR17SA	LR27SA	LR37SA	LR47SA	LR57SA	LR67SA	_			
1												
4		BlueKote® Form 7	L17-TB	L27-TB	L37-TB	L47-TB	L57-TB	L67-TB	_	_	_	_
		BlueKote® Form 7	TB17-TB	TB27	TB37	TB47	TB57	TB67				_
		BlueKote® Form 8*	TB18	TB28	TB38	TB448	TB58	TB68	_	_	_	_
	TB	Series 35	TB50M	TB75M	TB100M	TB125M	TB150M	TB200M	_	_	_	_
		Sand Cast Aluminum Form 7	TB17SA	TB27SA	TB37SA	TB47SA	TB57SA	TB67SA	_	_	_	_
		Stainless Steel Form 8	TB18SST	TB28SST	TB38SST	TB48SST	TB58SST	TB68SST	(with o	overs, ga	skets and scr	ews)
000		BlueKote® Form 7	X17	X27	X37	X47	X57	X67	_	_	_	_
		BlueKote® Form 8*	X18	X28	X38	X448	X58	X68	_	_	_	_
-	X	Series 35	X50M	X75M	X100M	X125M	X150M	X200M	_	_	_	_
100		Sand Cast Aluminum Form 7	X17SA	X27SA	X37SA	X47SA	X57SA	X67SA	_	_	_	_
		Guerrasimiani omi		,,_,,,,,	,,,,,,,,,,	7	,,	7.07011				
	E	BlueKote® Form 7	E17	E27	E37	_	_	_	_	_	_	_
		•										

<sup>\* 1/2&</sup>quot; through 11/4" have (2) mounting holes; 11/2" through 4" have (4) mounting holes

TA BlueKote® Form 7



TA37

TA47

TA17

TA27

Fax: 901.252.1354

TA57

TA67

E-74