



Product Datasheet



ANDERSON FARGO

GLT1316A -- Automatic Splice



Automatic Splice, Full Tension, for ACSR, Dia. Range Consult Fargo - Consult Fargo

Product Specifications

<p>Splice Type</p>	 <p>Automatic Splices</p>
<p>Automatic Splice Series</p>	 <p>GLT-400 Series Automatic Splice Aluminum Full Tension AAC, AAAC & ACSR Conductor Multiple Layer Al Strand Conductor</p>
<p>PDF Catalog Page</p>	<p>Click HERE to view the web page.</p>
<p>Conductor Type</p>	<p>AAC, AAAC, ACSR</p>
<p>Conductor Diameter (Minimum)</p>	<p>0.609 in</p>
<p>Conductor Diameter (Maximum)</p>	<p>0.642 in</p>
<p>Automatic Conductor Range</p>	<p>266.8 (26/7) ACSR</p>
<p>Material</p>	<p>Aluminum</p>
<p>Gripper Material</p>	<p>Aluminum Alloy</p>
<p>Minimum Conductor Diameter</p>	<p>0.609 in</p>
<p>Maximum Conductor Diameter</p>	<p>0.642 in</p>
<p>Outside Diameter</p>	<p>0.609 - 0.642 in (15.50 - 16.34 mm)</p>
<p>Dimension A</p>	<p>38 in (890 mm)</p>
<p>Dimension B</p>	<p>2.2 in (57 mm)</p>
<p>UL Listed</p>	<p>No</p>
<p>Inhibitor Loaded</p>	<p>Yes</p>
<p>Color Code</p>	<p>Natural</p>
<p>Material Type</p>	<p>Standard</p>
<p>UPC Code</p>	<p>09635931228</p>
<p>Standard Package</p>	<p>5</p>
<p>Standard Package Unit</p>	<p>Each</p>

Min Order Qty	5
Weight / Ea.	7.252 lbs

Notes

ANSI C119.4, Class A connector, Consult Factory for conductor sizes not listed.

Features

Individually bagged to seal out dirt before use.

Compressed Product Number

GLT1316A



Ref Dimension A & B



Inside an Automatic Splice.

[Catalog Home](#)



[Warranty Info](#) | [Trademarks](#) | [Terms of Use](#)

All contents Copyright © 2007 Hubbell Power Systems, Inc. All rights reserved.

NOTE: Because Hubbell has a policy of continuous product improvement, we reserve the right to change design and specifications without notice.