



[Catalog Home](#)

Product Datasheet



ANDERSON FARGO

GL4042A11 -- Automatic Splice



Automatic Splice, Bimetallic, 2 & 4 Stranded AAC, AAAC, ACSR to 6 Solid Copper

Product Specifications

<p>Splice Type</p>	 <p>Automatic Splices</p>
<p>Automatic Splice Series</p>	 <p>GL Series Automatic Splice Bi-Metal (Copper to Aluminum) AAC, AAAC, ACSR & Copper Conductor</p>
<p>PDF Catalog Page</p>	<p>Click HERE to view the web page.</p>
<p>Material</p>	<p>Aluminum/Copper</p>
<p>Dimension A</p>	<p>9.4 in (239 mm)</p>
<p>Dimension B</p>	<p>1.0 in (25 mm)</p>
<p>UL Listed</p>	<p>No</p>
<p>Inhibitor Loaded</p>	<p>Yes</p>
<p>Color Code</p>	<p>None</p>
<p>Material Type</p>	<p>Non-Standard</p>
<p>UPC Code</p>	<p>09635931194</p>
<p>Standard Package</p>	<p>25</p>
<p>Standard Package Unit</p>	<p>Each</p>
<p>Min Order Qty</p>	<p>25</p>
<p>Weight / Ea.</p>	<p>0.392 lbs</p>

Notes


Rated for 95% RBS of weaker conductor, Consult factory for conductor sizes not listed.

Features

Individually bagged to seal out dirt before use.

Compressed Product Number

GL4042A11



Ref Dimension A & B

[Catalog Home](#)



[Warranty Info](#) | [Trademarks](#) | [Terms of Use](#)

All contents Copyright © 2007 Hubbell Power Systems, Inc. All rights reserved.

NOTE: Because Hubbell has a policy of continuous product improvement, we reserve the right to change design and specifications without notice.