Carb & Choke Cleaner

I. Product Description

CRC Carb & Choke Cleaner is a fast-acting carburetor and choke cleaner that dissolves carburetor deposits such as sludge, gum and varnish. Its low VOC formula is designed to maximize carburetor performance, improve fuel system performance and ensure maximum fuel economy.

II. Applications

Recommended for cleaning automatic chokes, carburetor elements, intake parts and ventilating systems. Suitable for general purpose cleaning of non-painted surfaces.

III. Features & Benefits

- Effectively Dissolves Harmful Deposits. Removes gum, sludge and varnish that inhibit performance.
- Fast-Acting. Efficient cleaning action.
- Safe for Equipment. Will not harm oxygen sensors or catalytic converters.
- Low VOC Formula. Reduces contributions to ground smog. Meets U.S. EPA and CA VOC requirements.
- Improves Fuel System Performance. Ensures maximum fuel economy.
- M.S.D.[L.]™-Material Safety Data Label. Provides instant access to current safety information should an accident or OSHA inspection occur. Helps comply with OSHA Hazard Communications Standard 29 CFR 1910.1200.

IV. Physical Properties without propellant

Flash Point	<0°F TCC
Odor	Aromatic
Appearance	Clear, colorless liquid
Vapor Density	Heavier than air
Vapor Pressure	Not Determined
VOC Content (Fed)	366 g/L
Sara Title III, Sect. 313 Chemicals	Yes
Prop 65	Yes

Boiling Point	131°F (initial)
Solubility	Slight in H ₂ O
VOC %	43.5%
Specific Gravity	0.815
Freezing Point	Not Determined
рН	N/A
% VOC	45%
Propellant	Carbon Dioxide

V. Specifications and Approvals

Not applicable.

VI. Performance Characteristics

Not applicable.

VII. Directions

Read all directions before using this product. Use plastic extension tube to direct spray to exact location.

CARBURETOR AND LINKAGE

- With ignition off and engine cool, remove air filter and entire exterior surface of carburetor including linkage.
- After carburetor dries, start engine and spray **CRC Carb & Choke Cleaner** down the carburetor throat to remove the deposits from the lower throttle plate area.

AUTOMATIC CHOKES

 With engine off, spray CRC Carb & Choke Cleaner on both ends of choke valve and corresponding linkages while opening and closing choke by hand.

MANIFOLD HEAT CONTROL VALVE

- With engine cold, spray CRC Carb & Choke Cleaner on both ends of heat control valve shaft.
- Move counterweight up and down until valve moves freely. If necessary, tap gently with a light hammer to loosen a frozen heat control valve.

PCV VALVES

Disconnect crank case side of PCV valve and, with the engine running, spray CRC Carb & Choke Cleaner into open end of valve while working the plunger back and forth.

IMPORTANT

* If spilled or sprayed on painted surface, wipe off or wash off immediately.

VIII. Package Description

Part Number	Container Size
03077	16 oz Aerosol

IV. Disposal

Disposal requirements vary by state and local jurisdiction. All used and unused product should be disposed of in conformance with local, state and federal regulations.

X. Special Use Warnings

Aerosol Cans

Contents extremely flammable. Do not smoke while spraying. Extinguish all flames, pilot lights, and heaters. Do not puncture, incinerate or store above 120° F. Exposure to high temperatures may cause can to burst. Do not place in direct sunlight or near any heat source. Aerosol cans will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

General

Use only in well ventilated area. Ventilation may be improved by opening a window or door or providing mechanical assistance. Vapors will accumulate readily and may ignite. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. If ventilation is not adequate, respiratory protection should be worn. For more information regarding short term and long term exposure, review this product's Material Safety Data Sheet.

DISCLAIMER: This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. All products should be tested for suitability on a particular application prior to actual use. CRC Industries, Inc. makes no representations or warranties of any kind concerning this data.

CRC Industries, Inc. Technical Service: (800)521-3168 Industrial Products Division Customer Service: (800)272-4620 Warminster, PA 18974 CRC On-Line: (215)442-6260