

# 9070T2000D31

## XFMR CONTROL 2000VA

### MULTIPLEVOLTAGES

Product availability : Stock - Normally stocked in distribution facility



Price\* : 1358.00 USD



#### Main

Product or component type	Industrial Control Transformer
Rated power in VA	2000 VA
Primary voltage	240 x 480 V 230 x 460 V 220 x 440 V
Secondary voltage	120/240 V 115/230 V 110/220 V
Range of product	T

#### Complementary

Phase	1 phase
Rated power in VA	2000 VA per UL 2000 VA per CSA 2000 VA per NOM 1500 VA per CE
Primary voltage	220 x 440 V : 110/220 V 230 x 460 V : 115/230 V 240 x 480 V : 120/240 V
Temperature rise	115 °C
Electrical connection	Screw clamp terminals
Height	6.17 in
Width	7.06 in
Depth	7.17 in
Material	Copper winding
Product compatibility	FSC2

## Environment

Product certifications	CE UL listed file E61239 CSA file LR37055 guide 184-N-90
NEMA degree of protection	Not rated (open device)
Insulation temperature	356 °F (180 °C)

## Ordering and shipping details

Category	16201 - 9070 T (NOT TF) 250-2000VA
Discount Schedule	CP8
GTIN	00785901803546
Nbr. of units in pkg.	1
Package weight(Lbs)	50
Returnability	Y
Country of origin	US

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1227 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

## Contractual warranty

Warranty period	10 years
-----------------	----------