


NOTE: DUTY CYCLE VOLTAGE RATING - 9 KV RMS

| | | | | | | | |
|-----------------------|---------------------------------------|--|--------|------|-------|-------|-------|
| .5 μ SEC IR kV | 5kA 500 A SWITCHING SURGE IR kV | MAXIMUM 8/20 DISCHARGE VOLTAGE - kV AT | | | | | |
| | | 1.5 kA | 3.0 kA | 5 kA | 10 kA | 20 kA | 40 kA |
| 33.5 | 23.0 | 26.0 | 28.0 | 30.0 | 33.0 | 39.0 | 50.5 |

| | | | |
|--|---|-----------------------------------|-------------------------------|
| CONFIDENTIAL: THIS DRAWING AND ITS CONTENTS ARE CONFIDENTIAL AND THE EXCLUSIVE PROPERTY OF HUBBELL POWER SYSTEMS. NO PUBLICATION, DISTRIBUTION OR COPIES MAY BE MADE WITHOUT THE WRITTEN CONSENT OF HUBBELL POWER SYSTEMS. HUBBELL POWER SYSTEMS UNPUBLISHED ALL RIGHTS RESERVED UNDER THE COPYRIGHT LAWS. |  HUBBELL® POWER SYSTEMS | | |
| | TITLE ELBOW ARRESTER 7.65 KV MCOV | | |
| SIZE S | DWG NO. -- | CAT / PART / ASSY NO. 215ELA09 | REV 0 |
| REV DATE 07/29/09 | DO NOT SCALE THIS DRAWING | DRN BY JVR | DATE 07/29/09 SHEET 1 OF 1 |