



**BURNDY Catalog Number**  
**UPC Number**

HSB316T6PF18  
7818102145277  
HTSHRKN THIN 3/16DIA 6IN,#18-12 STR  
Active

**Description**  
**Status**

**Web Use**  
BURNDY Product Line

**Dimensional**

Operating Temperature Range - (F) -67 - 275  
Shrink Temperature (C) 120  
Conductor Range #18-12  
Wall Thickness - Recovery 0.09  
Wall Thickness 0.020  
Dimension (Max Before Shrink) 0.19  
Wall Thickness - Exp 0.020  
Opening Temperature Range - (C) -55 - 135

**General**

**Product Description**

Thin Wall Cross-Linked Polyolefin  
Heat Shrink Tubing, #12-18 AWG,  
600 V, 6.00" L, Flame Retardant,  
All Black

**Conductor(s)**

Nominal Diameter (Fraction) 3/16

**Physical**

Shrink Ratio 2:1  
Color Black

**Approvals / Certifications**

ROHS Compatible Compliant  
UL Listed N  
UL Recognized Y  
CULUS N

**Documentation**

For further technical assistance, please contact us

**BURNDY LLC - USA**

47 East Industrial Park Drive  
Manchester NH 03109

**BURNDY Technical Services**

47 East Industrial Park Drive  
Manchester NH 03109

Hours: 8:00 AM - 5:00 PM  
Monday - Friday  
Phone: 800-346-4175