

# ZB4BZ102

single contact block with body/fixing collar 1NC  
screw clamp terminal

Product availability : Stock - Normally stocked in distribution facility



## Main

|                               |  |
|-------------------------------|--|
| Range of product              | Harmony XB4  |
| Product or component type     | Complete body/contact assembly   |
| Device short name             | ZB4  |
| Fixing collar material        | Zamak  |
| Sale per indivisible quantity | 1  |
| Contacts type and composition | 1 NC   |
| Contact operation             | Slow-break   |
| Contact block type            | Single   |
| Device composition            | Fixing collar<br>Body  |
| Connections - terminals       | Screw clamp terminals: $\leq 2 \times 1.5 \text{ mm}^2$ with cable end conforming to EN 60947-1<br>Screw clamp terminals: $\geq 1 \times 0.22 \text{ mm}^2$ without cable end conforming to EN 60947-1 |

## Complementary

|                               |   |
|-------------------------------|---|
| CAD overall width             | 1.18 in (30 mm)   |
| CAD overall height            | 1.85 in (47 mm)   |
| CAD overall depth             | 1.46 in (37 mm)   |
| Terminals description ISO n°1 | (11-12)NC   |
| Product weight                | 0.12 lb(US) (0.053 kg)  |
| Contacts usage                | Standard contacts   |
| Positive opening              | With positive opening conforming to EN/IEC 60947-5-1 appendix K   |
| Operating travel              | 0.06 in (1.5 mm) (NC changing electrical state)<br>0.17 in (4.3 mm) (total travel)                          |
| Operating force               | 2 N (NC changing electrical state)  |
| Mechanical durability         | 5000000 cycles  |
| Tightening torque             | 7.08...10.62 lbf.in (0.8...1.2 N.m) conforming to EN 60947-1  |
| Shape of screw head           | Cross head compatible with Philips no 1 screwdriver<br>Cross head compatible with pozidriv No 1 screwdriver |

|  |  |
|--|--|
|  | Slotted head compatible with flat Ø 4 mm screwdriver<br>Slotted head compatible with flat Ø 5.5 mm screwdriver   |
| Contacts material  | Silver alloy (Ag/Ni)   |
| Short-circuit protection                                 | 10 A cartridge fuse type gG conforming to EN/IEC 60947-5-1   |
| [I <sub>th</sub> ] conventional free air thermal current | 10 A conforming to EN/IEC 60947-5-1  |
| [U <sub>i</sub> ] rated insulation voltage               | 600 V (degree of pollution: 3) conforming to EN 60947-1  |
| [U <sub>imp</sub> ] rated impulse withstand voltage      | 6 kV conforming to EN 60947-1  |
| [I <sub>e</sub> ] rated operational current              | 3 A at 240 V, AC-15, A600 conforming to EN/IEC 60947-5-1<br>6 A at 120 V, AC-15, A600 conforming to EN/IEC 60947-5-1<br>0.1 A at 600 V, DC-13, Q600 conforming to EN/IEC 60947-5-1<br>0.27 A at 250 V, DC-13, Q600 conforming to EN/IEC 60947-5-1<br>0.55 A at 125 V, DC-13, Q600 conforming to EN/IEC 60947-5-1<br>1.2 A at 600 V, AC-15, A600 conforming to EN/IEC 60947-5-1   |
| Electrical durability                                    | 10000000 cycles, AC-15, 2 A at 230 V, operating rate: 3600 cyc/h, load factor: 0.5 conforming to EN/IEC 60947-5-1 appendix C<br>10000000 cycles, AC-15, 3 A at 120 V, operating rate: 3600 cyc/h, load factor: 0.5 conforming to EN/IEC 60947-5-1 appendix C<br>10000000 cycles, AC-15, 4 A at 24 V, operating rate: 3600 cyc/h, load factor: 0.5 conforming to EN/IEC 60947-5-1 appendix C<br>10000000 cycles, DC-13, 0.2 A at 110 V, operating rate: 3600 cyc/h, load factor: 0.5 conforming to EN/IEC 60947-5-1 appendix C<br>10000000 cycles, DC-13, 0.5 A at 24 V, operating rate: 3600 cyc/h, load factor: 0.5 conforming to EN/IEC 60947-5-1 appendix C |
| Electrical reliability                                   | $\Lambda < 10\text{exp}(-6)$ at 5 V, 1 mA in clean environment conforming to EN/IEC 60947-5-4<br>$\Lambda < 10\text{exp}(-8)$ at 17 V, 5 mA in clean environment conforming to EN/IEC 60947-5-4  |

## Environment

|                                       |  |
|---------------------------------------|--|
| Protective treatment                  | TH   |
| Ambient air temperature for storage   | -40...158 °F (-40...70 °C)   |
| Ambient air temperature for operation | -40...158 °F (-40...70 °C)   |
| IP degree of protection               | IP20 conforming to IEC 60529   |
| Standards                             | EN/IEC 60947-5-4<br>JIS C 4520<br>UL 508<br>EN/IEC 60947-5-5<br>EN/IEC 60947-5-1<br>EN/IEC 60947-1<br>CSA C22.2 No 14  |
| Product certifications                | RINA<br>GL<br>DNV<br>UL<br>BV<br>CSA<br>LROS (Lloyds register of shipping)   |
| Vibration resistance                  | 5 gn (f = 2...500 Hz) conforming to IEC 60068-2-6  |
| Shock resistance                      | 30 gn (duration = 18 ms) half sine wave acceleration conforming to IEC 60068-2-27<br>50 gn (duration = 11 ms) half sine wave acceleration conforming to IEC 60068-2-27 |

## Ordering and shipping details

|                       |   |
|-----------------------|---|
| Category              | 22469 - PUSHBUTTON,22MM ACCESSORIES-NEW |
| Discount Schedule     | CS2                                     |
| GTIN                  | 00785901370185                          |
| Nbr. of units in pkg. | 1                                       |
| Package weight(Lbs)   | 0.11                                    |
| Returnability         | Y                                       |
| Country of origin     | FR                                      |

## Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|