



BURNDY Catalog Number
UPC Number
Description
Status

YAZV262TC38FX
 7818101353277
 CULUG-2/0FX-LONG/SKV-3/8
 Active

Web Use
 BURNDY Product Line

Dimensional

Tongue Angle
 Strip Length
 Length (in)
 Barrell Style
 Bolt Hole Size (in)
 Barrel Type
 Thickness
 B Length (in)
 Pad Width (in)
 E - in

Straight
 1-9/16
 3.76
 Skived
 Long
 0.13
 1.50
 0.93
 1.00

General

Number of Holes

 Product Description

2
 Cu Comp Terminal Flex Cond, Bvl
 Entry, 2 Hole/W/InspWindow, 2/0
 Weld,2/0(325/#24)DLO Flex, 2/0
 AWG Code, 600 V-35 kV, 3/8"
 Stud, 1.00" Spacing, Lng bbl

Conductor(s)

Copper Solid Size (Range)
 Navy Cable Size (Range)
 Copper Stranded (Range)

N/A
 N/A
 2/0 AWG

Physical

Type of Plating
 Bolt Hole Size
 Color Code
 Plated (Yes or No)
 Index Number
 Product Material

Tin
 3/8
 Black
 Y
 13
 Copper

Approvals / Certifications

UL Listed
 CSA Certified
 ROHS Compatible
 UL Recognized
 CULUS

Y
 Y
 Compliant
 N
 N

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM

Monday - Friday

Phone: 800-346-4175