Product data sheet Characteristics

ZB4BW113

white projecting illuminated pushbutton head \varnothing 22 spring return for integral LED

Product availability: Stock - Normally stocked in distribution facility



Main

		4
Range of product	Harmony XB4	
Product or component type	Head for illuminated push-button	
Device short name	ZB4	
Product compatibility	Integral LED	-
Bezel material	Chromium plated metal	
Mounting diameter	0.87 in (22 mm)	
Sale per indivisible quantity	1	
Shape of signaling unit head	Round	
Type of operator	Spring return	
Operator profile	White projecting unmarked	
Operator additional information	With plain lens	

Complementary

CAD overall width	1.14 in (29 mm)	
CAD overall height	1.14 in (29 mm)	
CAD overall depth	1.3 in (33 mm)	
Product weight	0.06 lb(US) (0.029 kg)	
Resistance to high pressure washer	1015.26 psi (7000000 Pa) at 131 °F (55 °C),distance: 0.1 m	
Mechanical durability	10000000 cycles	
lectrical composition code M1 <= 6 contacts using single blocks in front mounting with integral LED M2 <= 6 contacts using single and double blocks in front mounting with integral LED M10 <= 2 contacts using single blocks in front mounting with integral LED M6 <= 2 contacts using single blocks in front mounting with integral LED and transformer		

Environment

Destanti e tranto est	TU	Ĕ
Protective treatment	In	ā
Ambient air temperature for storage	-40158 °F (-4070 °C)	<u>n</u>

Ambient air temperature for operation	-40158 °F (-4070 °C)	
Overvoltage category	Class I conforming to IEC 60536	
IP degree of protection	IP69 IP66 conforming to IEC 60529 IP69K	
NEMA degree of protection	NEMA 13 NEMA 4X	
IK degree of protection	IK05 conforming to EN 50102	
Standards	EN/IEC 60947-5-5 CSA C22.2 No 14 EN/IEC 60947-5-4 UL 508 EN/IEC 60947-1 EN/IEC 60947-5-1 JIS C 4520	
Product certifications	GL LROS (Lloyds register of shipping) CSA RINA UL listed DNV BV	
Vibration resistance	5 gn (f = 2500 Hz) conforming to IEC 60068-2-6	
Shock resistance	30 gn (duration = 18 ms) half sine wave acceleration conforming to IEC 60068-2-27 50 gn (duration = 11 ms) half sine wave acceleration conforming to IEC 60068-2-27	

Ordering and shipping details

Category	22468 - PUSHBUTTONS,22MM(METAL) NEW		
Discount Schedule	CS2		
GTIN	00785901376422		
Nbr. of units in pkg.	1		
Package weight(Lbs)	5.9999999999998E-2		
Returnability	Υ		
Country of origin	FR		

Contractual warranty

Warranty period	18 months	