Product data sheet Characteristics

ZB5AL4

red projecting pushbutton head Ø22 spring return unmarked

Product availability: Stock - Normally stocked in distribution facility



Main

| Range of product | Harmony XB5 |
|-------------------------------|--------------------------------------|
| Product or component type | Head for non-illuminated push-button |
| Device short name | ZB5 |
| Bezel material | Plastic |
| Mounting diameter | 0.87 in (22 mm) |
| Sale per indivisible quantity | 1 |
| Shape of signaling unit head | Round |
| Type of operator | Spring return |
| Operator profile | Red projecting unmarked |

Complementary

| o o mpio mornary | | 9 |
|-----------------------------|--|--|
| CAD overall width | 1.14 in (29 mm) | |
| CAD overall height | 1.14 in (29 mm) | |
| CAD overall depth | 1.3 in (33 mm) | <u></u> |
| Product weight | 0.04 lb(US) (0.019 kg) | <u></u> |
| Mechanical durability | 10000000 cycles | in the state of th |
| Station name | XALD 15 cut-outs XALK 25 cut-outs | a substi |
| Electrical composition code | C1 <= 9 contacts using single blocks in front mounting C2 <= 9 contacts using single and double blocks in front mounting C11 <= 3 contacts using single blocks in front mounting C15 1 contacts using single blocks in front mounting SF1 <= 3 contacts using single blocks in front mounting SR1 <= 3 contacts using single blocks in rear mounting | iation is not intended as |

Environment

| Protective treatment | TH | - <u>+</u> - |
|-------------------------------------|----------------------|--------------|
| Ambient air temperature for storage | -40158 °F (-4070 °C) | - 10 |

| Ambient air temperature for operation | -40158 °F (-4070 °C) |
|---------------------------------------|---|
| Overvoltage category | Class II conforming to IEC 60536 |
| IP degree of protection | IP69 IP67 IP66 conforming to IEC 60529 IP69K |
| NEMA degree of protection | NEMA 13 NEMA 4X |
| Resistance to high pressure washer | 1015.26 psi (7000000 Pa) at 131 °F (55 °C), distance: 0.1 m |
| IK degree of protection | IK03 conforming to IEC 50102 |
| Standards | CSA C22.2 No 14 EN/IEC 60947-5-1 UL 508 EN/IEC 60947-1 EN/IEC 60947-5-4 JIS C 4520 |
| Product certifications | UL listed CSA LROS (Lloyds register of shipping) DNV GL RINA BV |
| Shock resistance | 30 gn (duration = 18 ms) half sine wave acceleration conforming to IEC 60068-2-27 50 gn (duration = 11 ms) half sine wave acceleration conforming to IEC 60068-2-27 |
| Vibration resistance | 5 gn (f = 2500 Hz) conforming to IEC 60068-2-6 |

Ordering and shipping details

| eraering and emphing det | S. I.O. |
|--------------------------|---------------------------------------|
| Category | 22467 - PUSHBUTTONS,22MM(PLASTIC) NEW |
| Discount Schedule | CS2 |
| GTIN | 00785901906452 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 4.00000000000001E-2 |
| Returnability | Υ |
| Country of origin | FR |
| | |

Contractual warranty

| · · · · · · · · · · · · · · · · · · · | |
|---------------------------------------|-----------|
| Warranty period | 18 months |