Product data sheet Characteristics

ZB4BV07

clear pilot light head \emptyset 22 with plain lens for BA9s bulb

Product availability: Stock - Normally stocked in distribution facility



Main

Range of product	Harmony XB4	
Product or component type	Head for pilot light	
Product compatibility	BA 9s	
Device short name	ZB4	
Bezel material	Chromium plated metal	
Mounting diameter	0.87 in (22 mm)	
Sale per indivisible quantity	1	
Shape of signaling unit head	Round	·
Cap/Operator or lens colour	Clear	
Operator additional information	With plain lens	

Complementary

CAD overall width	1.14 in (29 mm)	 •
CAD overall height	1.14 in (29 mm)	
CAD overall depth	1.22 in (31 mm)	
Product weight	0.06 lb(US) (0.027 kg)	, <u>,</u> 4
Resistance to high pressure washer	1015.26 psi (7000000 Pa) at 131 °F (55 °C),distance: 0.1 m	-
Electrical composition code	P3 in front mounting with BA 9s P4 in front mounting with BA 9s and transformer	ט ט ס ב
Main group	Pilot light	
Group of product	Lens fitted BA9s	
Cap/Operator or lens colour	Clear	
Compatibility code	ZB4	pentat

Environment

Protective treatment	TH		

Ambient air temperature for storage	-40158 °F (-4070 °C)	
Ambient air temperature for operation	-40131 °F (-4055 °C)	
Overvoltage category	Class I conforming to IEC 60536	
Electrical shock protection class	Class I conforming to IEC 60536	
IP degree of protection	IP69 IP67 IP66 conforming to IEC 60529 IP69K	
NEMA degree of protection	NEMA 13 NEMA 4X	
IK degree of protection	IK06 conforming to IEC 50102	
Standards	EN/IEC 60947-5-4 JIS C 4520 EN/IEC 60947-5-5 EN/IEC 60947-1 UL 508 EN/IEC 60947-5-1 CSA C22.2 No 14	
Vibration resistance	5 gn (f = 2500 Hz) conforming to IEC 60068-2-6	
Shock resistance	30 gn (duration = 18 ms) half sine wave acceleration conforming to IEC 60068-2-27 50 gn (duration = 11 ms) half sine wave acceleration conforming to IEC 60068-2-27	

Ordering and shipping details

Category	22468 - PUSHBUTTONS,22MM(METAL) NEW
Discount Schedule	CS2
GTIN	00785901371557
Nbr. of units in pkg.	1
Package weight(Lbs)	5.00000000000000E-2
Returnability	Υ
Country of origin	FR

Contractual warranty

101	40
Warranty period	18 months
rrandy ponda	10 111011110