

# ZB4BK1353

orange illuminated selector switch head Ø22 3-position stay put

Product availability : Stock - Normally stocked in distribution facility



## Main

|                               |                                      |
|-------------------------------|--------------------------------------|
| Range of product              | Harmony XB4                          |
| Product or component type     | Head for illuminated selector switch |
| Product compatibility         | Integral LED                         |
| Device short name             | ZB4                                  |
| Bezel material                | Chromium plated metal                |
| Mounting diameter             | 0.87 in (22 mm)                      |
| Sale per indivisible quantity | 1                                    |
| Shape of signaling unit head  | Round                                |
| Type of operator              | Stay put                             |
| Operator profile              | Orange standard handle               |
| Operator position information | 3 positions +/- 45°                  |

## Complementary

|                                    |  |
|------------------------------------|--|
| CAD overall width                  | 1.14 in (29 mm)  |
| CAD overall height                 | 1.14 in (29 mm)  |
| CAD overall depth                  | 1.69 in (43 mm)  |
| Product weight                     | 0.08 lb(US) (0.036 kg)   |
| Resistance to high pressure washer | 1015.26 psi (7000000 Pa) at 131 °F (55 °C), distance: 0.1 m  |
| Mechanical durability              | 1000000 cycles   |
| Electrical composition code        | M10 <= 2 contacts using single blocks in front mounting with integral LED<br>M6 <= 2 contacts using single blocks in front mounting with integral LED and transformer<br>M3 <= 4 contacts using single blocks in front mounting with integral LED<br>M4 <= 4 contacts using single and double blocks in front mounting with integral LED |

## Environment

|                                     |                            |
|-------------------------------------|----------------------------|
| Protective treatment                | TH                         |
| Ambient air temperature for storage | -40...158 °F (-40...70 °C) |

|                                       |  |
|---------------------------------------|--|
| Ambient air temperature for operation | -40...158 °F (-40...70 °C)   |
| Overvoltage category                  | Class I conforming to IEC 60536  |
| Electrical shock protection class     | Class I conforming to IEC 60536  |
| IP degree of protection               | IP69<br>IP67<br>IP66 conforming to IEC 60529<br>IP69K  |
| NEMA degree of protection             | NEMA 13<br>NEMA 4X   |
| IK degree of protection               | IK06 conforming to IEC 50102   |
| Standards                             | UL 508<br>EN/IEC 60947-1<br>EN/IEC 60947-5-5<br>EN/IEC 60947-5-1<br>JIS C 4520<br>CSA C22.2 No 14<br>EN/IEC 60947-5-4  |
| Product certifications                | CSA<br>RINA<br>UL listed<br>DNV<br>BV<br>LROS (Lloyds register of shipping)<br>GL  |
| Vibration resistance                  | 5 gn (f = 2...500 Hz) conforming to IEC 60068-2-6  |
| Shock resistance                      | 30 gn (duration = 18 ms) half sine wave acceleration conforming to IEC 60068-2-27<br>50 gn (duration = 11 ms) half sine wave acceleration conforming to IEC 60068-2-27 |

## Ordering and shipping details

|                       |                                     |
|-----------------------|-------------------------------------|
| Category              | 22468 - PUSHBUTTONS,22MM(METAL) NEW |
| Discount Schedule     | CS2                                 |
| GTIN                  | 00785901373049                      |
| Nbr. of units in pkg. | 1                                   |
| Package weight(Lbs)   | 8.999999999999997E-2                |
| Returnability         | Y                                   |
| Country of origin     | FR                                  |

## Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|