

Product availability : Stock - Normally stocked in distribution facility



Main

Circuit breaker type	0 tandem
Cover type	Combination flush/surface cover
Device application	Value pack
Enclosure type	Enclosure for indoor
Module type	QOM2
Provided equipment	5 QO12 circuit breaker 1 QO132M200C circuit breaker
Range of product	QO

Complementary

[In] rated current	125 A
System Voltage	120/240 V AC
AWG gauge	AWG 4...AWG 2/0 aluminium/copper cable
Box number	8R
Depth	3.75 in
Height	26.04 in
Load center type	Main breaker
Material	Tin plated copper busbar
Network number of phases	1 phase
Number of spaces	32
Short-circuit protection	22 kA
Type of installation	Indoor
Width	14.25 in
Wiring configuration	3-wire

Environment

NEMA degree of protection	NEMA 1
Product certifications	UL listed

Ordering and shipping details

Category	00184 - MISC. QO 1PH LOAD CENTERS
Discount Schedule	DE3A
GTIN	00785901334514
Nbr. of units in pkg.	1
Package weight(Lbs)	27.68
Returnability	Y
Country of origin	US

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1411 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------