### Product data sheet Characteristics

## **ZB4BW353**

# orange flush illuminated pushbutton head $\emptyset$ 22 spring return for integral LED

Product availability: Stock - Normally stocked in distribution facility



#### Main

Range of product	Harmony XB4
Product or component type	Head for illuminated push-button
Device short name	ZB4
Product compatibility	Integral LED
Bezel material	Chromium plated metal
Mounting diameter	0.87 in (22 mm)
Sale per indivisible quantity	1
Shape of signaling unit head	Round
Type of operator	Spring return
Operator profile	Orange flush unmarked
Operator additional information	With plain lens

#### Complementary

CAD overall width	1.14 in (29 mm)	:
CAD overall height	1.14 in (29 mm)	
CAD overall depth	1.18 in (30 mm)	
Product weight	0.06 lb(US) (0.026 kg)	
Resistance to high pressure washer	1015.26 psi (7000000 Pa) at 131 °F (55 °C),distance: 0.1 m	
Mechanical durability	10000000 cycles	
Electrical composition code	M1 <= 6 contacts using single blocks in front mounting with integral LED M2 <= 6 contacts using single and double blocks in front mounting with integral LED M10 <= 2 contacts using single blocks in front mounting with integral LED M6 <= 2 contacts using single blocks in front mounting with integral LED and transformer	

#### Environment

Destanti e transcent	TU	Ĕ
Protective treatment	In	ā
Ambient air temperature for storage	-40158 °F (-4070 °C)	<u>n</u>

Ambient air temperature for operation	-40158 °F (-4070 °C)
Overvoltage category	Class I conforming to IEC 60536
IP degree of protection	IP69 IP67 IP66 conforming to IEC 60529 IP69K
NEMA degree of protection	NEMA 13 NEMA 4X
IK degree of protection	IK06 conforming to EN 50102
Standards	EN/IEC 60947-1 EN/IEC 60947-5-1 UL 508 JIS C 4520 EN/IEC 60947-5-5 CSA C22.2 No 14 EN/IEC 60947-5-4
Product certifications	UL listed CSA LROS (Lloyds register of shipping) GL BV RINA DNV
Vibration resistance	5 gn (f = 2500 Hz) conforming to IEC 60068-2-6
Shock resistance	30 gn (duration = 18 ms) half sine wave acceleration conforming to IEC 60068-2-27 50 gn (duration = 11 ms) half sine wave acceleration conforming to IEC 60068-2-27

#### Ordering and shipping details

<u> </u>	
Category	22468 - PUSHBUTTONS,22MM(METAL) NEW
Discount Schedule	CS2
GTIN	00785901353843
Nbr. of units in pkg.	1
Package weight(Lbs)	5.999999999998E-2
Returnability	Υ
Country of origin	FR

#### Contractual warranty

Warranty period	18 months