Product data sheet Characteristics

ZB4BW143 red projecting illuminated pushbutton head Ø22 spring return for integral LED

Product availability : Stock - Normally stocked in distribution facility



Main

Harmony XB4	-
Head for illuminated push-button	-
ZB4	-
Integral LED	-
Chromium plated metal	
0.87 in (22 mm)	
1	
Round	
Spring return	
Red projecting unmarked	
With plain lens	
1.14 in (20 mm)	
-	
M10 <= 2 contacts using single blocks in front mounting with integral LED	
M6 <= 2 contacts using single blocks in front mounting with integral LED and transformer	
ТН	
	Head for illuminated push-button ZB4 Integral LED Chromium plated metal 0.87 in (22 mm) 1 Round Spring return Red projecting unmarked With plain lens 1.14 in (29 mm) 1.3 in (33 mm) 0.06 lb(US) (0.029 kg) 1015.26 psi (700000 Pa) at 131 °F (55 °C),distance: 0.1 m 10000000 cycles M1 <= 6 contacts using single blocks in front mounting with integral LED

Complementary

CAD overall width	1.14 in (29 mm)
CAD overall height	1.14 in (29 mm)
CAD overall depth	1.3 in (33 mm)
Product weight	0.06 lb(US) (0.029 kg)
Resistance to high pressure washer	1015.26 psi (7000000 Pa) at 131 °F (55 °C),distance: 0.1 m
Mechanical durability	1000000 cycles
Electrical composition code	M1 <= 6 contacts using single blocks in front mounting with integral LED M2 <= 6 contacts using single and double blocks in front mounting with integral LED M10 <= 2 contacts using single blocks in front mounting with integral LED M6 <= 2 contacts using single blocks in front mounting with integral LED and transformer

Environment

Protective treatment	ТН
Ambient air temperature for storage	-40158 °F (-4070 °C)

Life Is On Schneider

Ambient air temperature for operation	-40158 °F (-4070 °C)
Overvoltage category	Class I conforming to IEC 60536
IP degree of protection	IP69 IP66 conforming to IEC 60529 IP69K
NEMA degree of protection	NEMA 13 NEMA 4X
IK degree of protection	IK05 conforming to EN 50102
Standards	EN/IEC 60947-5-4 JIS C 4520 CSA C22.2 No 14 EN/IEC 60947-5-5 EN/IEC 60947-1 UL 508 EN/IEC 60947-5-1
Product certifications	DNV RINA GL UL listed CSA BV LROS (Lloyds register of shipping)
Vibration resistance	5 gn (f = 2500 Hz) conforming to IEC 60068-2-6
Shock resistance	30 gn (duration = 18 ms) half sine wave acceleration conforming to IEC 60068-2-27 50 gn (duration = 11 ms) half sine wave acceleration conforming to IEC 60068-2-27

Ordering and shipping details

Category	22468 - PUSHBUTTONS,22MM(METAL) NEW
Discount Schedule	CS2
GTIN	00785901353904
Nbr. of units in pkg.	1
Package weight(Lbs)	5.99999999999998E-2
Returnability	Υ
Country of origin	FR

Contractual warranty

Warranty period

18 months