Product data sheet Characteristics

ZB4BW313

white flush illuminated pushbutton head \emptyset 22 spring return for integral LED

Product availability: Stock - Normally stocked in distribution facility



Main

		<u>.</u>
Range of product	Harmony XB4	
Product or component type	Head for illuminated push-button	
Device short name	ZB4	
Product compatibility	Integral LED	
Bezel material	Chromium plated metal	<u> </u>
Mounting diameter	0.87 in (22 mm)	
Sale per indivisible quantity	1	
Shape of signaling unit head	Round	
Type of operator	Spring return	
Operator profile	White flush unmarked	
Operator additional information	With plain lens	3

Complementary

CAD overall width	1.14 in (29 mm)	:
CAD overall height	1.14 in (29 mm)	
CAD overall depth	1.18 in (30 mm)	
Product weight	0.06 lb(US) (0.026 kg)	
Resistance to high pressure washer	1015.26 psi (7000000 Pa) at 131 °F (55 °C),distance: 0.1 m	
Mechanical durability	10000000 cycles	
Electrical composition code	ctrical composition code M1 <= 6 contacts using single blocks in front mounting with integral LED M2 <= 6 contacts using single and double blocks in front mounting with integral LED M10 <= 2 contacts using single blocks in front mounting with integral LED M6 <= 2 contacts using single blocks in front mounting with integral LED and transformer	

Environment

Destanti e transcent	TU	Ĕ
Protective treatment	In	ā
Ambient air temperature for storage	-40158 °F (-4070 °C)	<u>n</u>

Ambient air temperature for operation	-40158 °F (-4070 °C)	
Overvoltage category	Class I conforming to IEC 60536	
IP degree of protection	IP69 IP67 IP66 conforming to IEC 60529 IP69K	
NEMA degree of protection	NEMA 13 NEMA 4X	
IK degree of protection	IK06 conforming to EN 50102	
Standards	CSA C22.2 No 14 JIS C 4520 EN/IEC 60947-1 EN/IEC 60947-5-1 EN/IEC 60947-5-5 UL 508 EN/IEC 60947-5-4	
Product certifications	DNV BV LROS (Lloyds register of shipping) GL UL listed CSA RINA	
Vibration resistance	5 gn (f = 2500 Hz) conforming to IEC 60068-2-6	
Shock resistance	30 gn (duration = 18 ms) half sine wave acceleration conforming to IEC 60068-2-27 50 gn (duration = 11 ms) half sine wave acceleration conforming to IEC 60068-2-27	

Ordering and shipping details

ordoring and ompping dotailo	
Category	22468 - PUSHBUTTONS,22MM(METAL) NEW
Discount Schedule	CS2
GTIN	00785901353812
Nbr. of units in pkg.	1
Package weight(Lbs)	5.999999999998E-2
Returnability	Y
Country of origin	FR

Contractual warranty

Warranty period	18 months