



A B C G R

► Models LP3E, LP3M, LP3P, LP3S, LP3T

# StreamLine® Low Profile Strobe Light

Model LP3 is offered in five mounting configurations. The LP3S features a three-hole surface mount — ideal for control panels and other flat or flush surfaces. The LP3E features a standard A-19 medium Edison screw-in base. The LP3M features a 1/2" NPT male pipe mount and 18" wire leads. LP3P features an integrated 1/2-inch NPT pipe mount. The "T-mount" LP3T has a popular 2-hole design for wall or flush mounting.

Models LP3M, LP3S and LP3T include a surface gasket to complete the Type 4X installation. An optional dome guard is available for use with the LP3M, LP3S and LP3T when installed flush with a panel. All LP3 units feature a threaded screw-on lens to allow for tool free wiring and strobe tube replacement.

StreamLine® strobes feature high-quality, long-life strobe tubes which are designed to reduce tungsten build-up for longer lamp maintenance cycles. Careful consideration is given to the relationship between tube shape and lens design for maximum light output. The high-quality dry-electrolyte capacitor used in StreamLine products runs cooler than those used in many competitive strobes, resulting in a more reliable product that won't fail due to overheating.

## FEATURES

- Available in 12-48VDC, 120VAC and 240VAC; LP3E only available in 120VAC
- Edison mount (E), 1/2" NPT male pipe mount (M), Surface mount (S), T-mount (T), integrated 1/2-inch NPT pipe mount (P)
- Five dome colors: Amber, Blue, Clear, Green and Red
- Screw-on lens provides easy access
- Low profile — Model LP3S is only 5" high
- Models LP3M, LP3P and LP3S are Type 4X, IP66, IP69K enclosure  
Models LP3E and LP3T are Type 4X, IP66 only
- PLC and triac compatible
- UL and cUL Listed and CSA Certified

MODEL	VOLTAGE	OPERATING CURRENT	FLASH RATE/ MINUTE	LIGHT OUTPUT PEAK <sup>1</sup>	ECP <sup>2</sup>
<b>LP3*-012-048**</b>	12-48VDC	0.44-0.10 amps	80 (+/-15)	175,000 cd	51.5 cd
<b>LP3*-120**</b>	120VAC	0.10 amps	80 (+/-15)	175,000 cd	51.5 cd
<b>LP3*-240**</b>	240VAC	0.07 amps	80 (+/-15)	175,000 cd	51.5 cd


\* Indicates Mounting Style: (E) Edison A-19 Screw-in Base, (M) Male Pipe Mount, (P) Pipe Mount, (S) Surface Mount, (T) T-Mount

\*\* Indicates color: (A) Amber, (B) Blue, (C) Clear, (G) Green or (R) Red

<sup>1</sup> Peak candela is the maximum light intensity generated by a flashing light during its light pulse

<sup>2</sup> ECP (Effective Candela) is the intensity that would appear to an observer if the light were burning steadily

# StreamLine® Low Profile Strobe Light (LP3E, LP3M, LP3P, LP3S, LP3T)



\*LP3T-120 & 240VAC shown, 24VDC wires protrude from side of base.

## SPECIFICATIONS


Lamp Life:	4,000 Hours	
Light Source:	Strobe tube	
Operating Temperature:	-31°F to 150°F	-35°C to 66°C
Net Weight:	7.3 oz	0.21 kg
Shipping Weight:	8.5 oz	0.24 kg
Diameter:	3.13"	79.5 mm
Height:		
LP3E	6.06"	153.9 mm
LP3M	5.82"	147.8 mm
LP3P	5.82"	147.8 mm
LP3S	5.02"	127.5 mm
LP3T	5.02"	127.5 mm

## REPLACEMENT PARTS

Description	Part Number
Lens, Amber	K8589063A
Lens, Blue	K8589063A-01
Lens, Clear	K8589063A-02
Lens, Green	K8589063A-03
Lens, Red	K8589063A-04
Flash Tube Assembly	K149130A
Gasket Kit <sup>1</sup>	K858900353A

<sup>1</sup> Includes gasket for LP3S and LP3T

## HOW TO ORDER



\*LP3E only available in 120VAC

## OPTIONAL ACCESSORIES

Description	Part Number
Wire Dome Guard for LP3M, LP3S and LP3T	LP3G

