



YDS49R49RS

Catalog ID: YDS49R49RS

Prop 65 Notice

Two-piece, full tension ACSR splice consists of steel inner sleeve and aluminum outer sleeve. ANSI C119.4 Class 1 (Full Tension)

Product Details

General

Connector Type	Splice
Die Index	419;422
Die Index - Element A	419
Die Index - Element B	422
Material	Aluminum
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	Y
Trade Name	HYSPLICE™
UPC	781810042434

Dimensions

Dimension - L Length Overall mm	254 mm
Dimension - Length Overall inch	10 in
Dimension - Steel Sleeve Length inch	10 in

Conductor Related

Conductor - ACSR Str Size	1033.5 (54/7) Curlew
Conductor - ACSR Str Size Range	1033.5 (54/7) Curlew
Conductor - AL Str Size	1033.5
Conductor - AL Str Size Range	1033.5
Conductor Type	ACSR C Str-Size AL C Str-Size

Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	СМ
UL Listed	No

Logistics

Minimum Pack Quantity	1

For further technical assistance, please contact us

BURNDY Headquarters

47 East Industrial Park Drive Manchester, New Hampshire 03109 **Customer Service Hours:**

8 AM - 8 PM Eastern Monday-Friday Emergency Service 24-hours/365 Days

Phone: 1-800-346-4175

1-603-647-5299 (International)