



BURNDY Catalog Number
UPC Number
Description
Status

BIBD2508
7818102240699
250-10 TWO SIDED UNITAP
Active

Web Use
BURNDY Product Line

Width (in)
Hex Size (Key)
Length (in)
Height (in)

Dimensional

2.64
5/16
7.66
2.13

Min Voltage Rating

Electrical

600

Number of Ports
Number of Screws

General

8
8

Product Description

Aluminum Multiple Tap
Connector, Clear Insulated, 8 Port,
2 Sided Entry, 10 AWG-250 kcmil,
Al/Cu Rated

Aluminum Size (Range)
Copper Solid Size (Range)
Copper Stranded (Range)

Conductor(s)

8 AWG-250 kcmil
N/A
10 AWG-250 kcmil

Type of Hardware
Type of Plating
Insulation Type
Plated (Yes or No)
Product Material

Physical

Aluminum
Unplated
Plastisol
N
Aluminum

Rated for Direct Burial
UL Listed
CSA Certified
ROHS Compatible
UL Recognized
CULUS
Industry Standards

Approvals / Certifications

N
Y
Y
Compliant
N
N
UL468A-468B

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
Monday - Friday
Phone: 800-346-4175