



BURNDY Catalog Number
UPC Number

Description

Status

Web Use

BURNDY Product Line

BIBD43

7818102238577

14-4 TWO SIDED UNITAP,1.51 IN
L

Active

Screw Size

Width (in)

Hex Size (Key)

Length (in)

Height (in)

Min Voltage Rating

Number of Ports

Number of Screws

Product Description

Aluminum Size (Range)

Copper Solid Size (Range)

Copper Stranded (Range)

Type of Hardware

Type of Plating

Insulation Type

Plated (Yes or No)

Product Material

UL Listed

CSA Certified

Rated for Direct Burial

ROHS Compatible

UL Recognized

CULUS

Industry Standards

Documentation

Dimensional

1/4

1.50

1/8

1.51

1.25

Electrical

600

General

3

3

Aluminum Multiple Tap

Connector, Clear Insulated, 3 Port,

2 Sided Entry, 14-4 AWG, Al/Cu

Rated

Conductor(s)

8 AWG-4 AWG

N/A

14 AWG-4 Str

Physical

Aluminum

Unplated

Plastisol

N

Aluminum

Approvals / Certifications

Y

Y

N

Compliant

N

N

UL468A-468B

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
Monday - Friday
Phone: 800-346-4175