

# Straight Blade Devices



## 15 and 20 Ampere, 125 and 250 Volts




**15A 125V**  
NEMA 5-15R  
UL CSA  
0.5 HP




**20A 125V**  
NEMA 5-20R  
UL CSA  
1 HP

### Hubbell-PRO Extra Heavy Duty Specification Grade Receptacles


Duplex	Color	Catalog Number	
Smooth polycarbonate face, duplex, back and side wired. Assembled in USA.	Black	<b>5252BK</b>	<b>5352BK</b>
	Brown	<b>5252B</b>	<b>5352B</b>
	Gray	<b>5252G</b>	<b>5352G</b>
	Ivory	<b>5252I</b>	<b>5352I</b>
	Light Almond	<b>5252LA</b>	<b>5352LA</b>
	Red	<b>5252R</b>	<b>5352R</b>
	White	<b>5252W</b>	<b>5352W</b>
Finder groove polycarbonate face, duplex, back and side wired. Assembled in USA.	Black	<b>5262BLK</b>	<b>5362BLK</b>
	Blue	<b>5262BL</b>	<b>5362BL</b>
	Brown	<b>5262B</b>	<b>5362B</b>
	Gray	<b>5262G</b>	<b>5362G</b>
	Ivory	<b>5262I</b>	<b>5362I</b>
	Light Almond	<b>5262LA</b>	<b>5362LA</b>
	Red	<b>5262R</b>	<b>5362R</b>
	White	<b>5262W</b>	<b>5362W</b>




**5262B**




**5252AI**



**IG5352**



**5362IWR**



**5662GY**

### Hubbell-PRO Heavy Duty Specification Grade Receptacles

Duplex	Color	Standard Duplex		Isolated Ground <sup>A</sup>	
		15A 125V NEMA 5-15R	20A 125V NEMA 5-20R	15A 125V NEMA 5-15R	20A 125V NEMA 5-20R
Smooth polycarbonate face, duplex, back and side wired.	Black	<b>5252ABLK</b>	<b>5352ABLK</b>	-	-
	Brown	<b>5252AB</b>	<b>5352AB</b>	-	-
	Gray	<b>5252AG</b>	<b>5352AG</b>	<b>IG5252GY</b>	<b>IG5352GY</b>
	Ivory	<b>5252AI</b>	<b>5352AI</b>	<b>IG5252I</b>	<b>IG5352I</b>
	Light Almond	<b>5252ALA</b>	<b>5352ALA</b>	<b>IG5252LA</b>	<b>IG5352LA</b>
	Orange	-	-	<b>IG5252</b>	<b>IG5352</b>
	White	<b>5252AW</b>	<b>5352AW</b>	<b>IG5252W</b>	<b>IG5352W</b>
Smooth polycarbonate face, Tamper-Resistant, duplex, back and side wired.	Black	<b>5252BLKTR</b>	<b>5352BLKTR</b>	-	-
	Brown	<b>5252BTR</b>	<b>5352BTR</b>	-	-
	Gray	<b>5252GTR</b>	<b>5352GTR</b>	-	-
	Ivory	<b>5252ITR</b>	<b>5352ITR</b>	<b>IG5252ITR</b>	<b>IG5352ITR</b>
	Light Almond	<b>5252LATR</b>	<b>5352LATR</b>	-	-
	Orange	-	-	<b>IG5252TR</b>	<b>IG5352TR</b>
	White	<b>5252WTR</b>	<b>5352WTR</b>	<b>IG5252WTR</b>	<b>IG5352WTR</b>
Finder groove polycarbonate face, duplex, back and side wired.	Black	<b>5262ABLK</b>	<b>5362ABLK</b>	<b>CR5252IGBK</b>	<b>CR5352IGBK</b>
	Blue	<b>5262ABL</b>	<b>5362ABL</b>	-	<b>CR5352IGBL</b>
	Brown	<b>5262AB</b>	<b>5362AB</b>	-	-
	Gray	<b>5262AG</b>	<b>5362AG</b>	<b>CR5252IGGY</b>	<b>CR5352IGGY</b>
	Ivory	<b>5262AI</b>	<b>5362AI</b>	<b>CR5252IGI</b>	<b>CR5352IGI</b>
	Light Almond	<b>5262ALA</b>	<b>5362ALA</b>	-	-
	Orange	-	-	<b>CR5252IG</b>	<b>CR5352IG</b>
White	<b>5262AW</b>	<b>5362AW</b>	<b>CR5252IGW</b>	<b>CR5352IGW</b>	
Weather resistant, Finder groove nylon face, duplex, back and side wired.	Black	<b>5262BKWR</b>	<b>5362BKWR</b>	-	-
	Brown	<b>5262WR</b>	<b>5362WR</b>	-	-
	Gray	<b>5262GYWR</b>	<b>5362GYWR</b>	-	-
	Ivory	<b>5262IWR</b>	<b>5362IWR</b>	-	-
	White	<b>5262WWR</b>	<b>5362WWR</b>	-	-

Note: <sup>A</sup>See section N for additional information on isolated ground devices. See page A-47 for accessories and section O for wallplates. See page Tech-10 for Tamper and Weather Resistant descriptions. Horsepower ratings listed above are AC only.



**15A 250V**  
NEMA 6-15R  
UL CSA  
1.5 HP



**20A 250V**  
NEMA 6-20R  
UL CSA  
2 HP

### Hubbell-PRO 250V Heavy Duty Specification Grade Receptacles

Description	Color	Catalog Number	
Smooth nylon face, duplex, back and side wired.	Black	<b>5662BK</b>	<b>5462BK</b>
	Blue	<b>5662BL</b>	<b>5462BL</b>
	Brown	<b>5662B</b>	<b>5462B</b>
	Gray	<b>5662GY</b>	<b>5462GY</b>
	Green	<b>5662GN</b>	<b>5462GN</b>
	Ivory	<b>5662IV</b>	<b>5462IV</b>
	Light Almond	<b>5662LA</b>	<b>5462LA</b>
	Red	<b>5662R</b>	<b>5462R</b>
	White	<b>5662WHI</b>	<b>5462WHI</b>

Dimensions in Inches (mm)