

**Product Number:** 25385

**Order Abbreviation:** F84T12/D/HO

**General Description:** 100W, 84" MOL, T12 HO (800 mA) rapid start fluorescent lamp, Daylight phosphor, 6500K color temperature, 76 CRI



### Product Information

Abbrev. With Packaging Info.	F84T12DHO 15/CS 1/SKU
Actual Length (in)	81.909
Actual Length (mm)	2080.49
Average Rated Life (hr)	12000
Base	Recessed Double Contact
Bulb	T12
Color Rendering Index (CRI)	76
Color Temperature/CCT (K)	6500
Diameter (in)	1.593
Diameter (mm)	40.46
Industry Standards	ANSI C78.81 - 2001
Initial Lumens at 25C	6550
Mean Lumens at 25C	5305
Nominal Length (in)	84.000
Nominal Length (mm)	2133.60
Nominal Wattage (W)	100.00



### Footnotes

- Approximate initial lumens after 100 hours operation.
- The life ratings of fluorescent lamps are based on 3 hr. operating cycles under specified conditions and with ballast meeting ANSI specifications. If operating cycle is increased, there will be a corresponding increase in the average hours life.
- Minimum starting temperature is a function of the ballast; consult the ballast manufacturer.
- Average life rating at 12 hours operation per start is 18,000 hours.