


**Product Number:** 25353

**Order Abbreviation:** F64T12/D/HO

**General Description:** 80W, 64" MOL, T12 HO (800 mA) rapid start fluorescent lamp, Daylight phosphor, 6500K color temperature, 76 CRI



**\* Full Case Required**

#### Product Information

Abbrev. With Packaging Info.	F64T12DHO 30/CS 1/SKU
Actual Length (in)	61.909
Actual Length (mm)	1572.49
Average Rated Life (hr)	12000
Base	Recessed Double Contact
Bulb	T12
Color Rendering Index (CRI)	76
Color Temperature/CCT (K)	6500
Diameter (in)	1.593
Diameter (mm)	40.46
Industry Standards	ANSI C78.81 - 2001
Initial Lumens at 25C	4900
Mean Lumens at 25C	3969
Mean Lumens at 35C	3969
Nominal Length (in)	64.000
Nominal Length (mm)	1625.60
Nominal Wattage (W)	80.00



#### Footnotes

- Approximate initial lumens after 100 hours operation.
- The life ratings of fluorescent lamps are based on 3 hr. operating cycles under specified conditions and with ballast meeting ANSI specifications. If operating cycle is increased, there will be a corresponding increase in the average hours life.
- Minimum starting temperature is a function of the ballast; consult the ballast manufacturer.
- Average life rating at 12 hours operation per start is 18,000 hours.