



**Product Number:** 28417

**Order Abbreviation:** F84T12/CW

**General Description:** 70W, 84" MOL, T12 instant start Slimline fluorescent lamp, Cool White phosphor, 4200K color temperature, 60 CRI

**\* Full Case Required**

#### Product Information

Abbrev. With Packaging Info.	F84T12CW 15/CS 1/SKU
Actual Length (in)	82.000
Actual Length (mm)	2082.80
Average Rated Life (hr)	12000
Base	Single Pin
Bulb	T12
Color Rendering Index (CRI)	60
Color Temperature/CCT (K)	4200
Diameter (in)	1.593
Diameter (mm)	40.46
Industry Standards	ANSI C78.81 - 2001
Initial Lumens at 25C	5300
Mean Lumens at 25C	4664
Mean Lumens at 35C	4664
Nominal Length (in)	84.000
Nominal Length (mm)	2133.60
Nominal Wattage (W)	70.00

#### Footnotes

- Approximate initial lumens after 100 hours operation.
- The life ratings of fluorescent lamps are based on 3 hr. operating cycles under specified conditions and with ballast meeting ANSI specifications. If operating cycle is increased, there will be a corresponding increase in the average hours life.
- Minimum starting temperature is a function of the ballast; consult the ballast manufacturer.
- Average life rating at 12 hours operation per start is 18,000 hours.