



Product Number: 26404

Order Abbreviation: F64T12/D

General Description: 52W, 64" MOL, T12 instant start Slimline fluorescent lamp, Daylight phosphor, 6500K color temperature, 76 CRI

*** Full Case Required**

Product Information

Abbrev. With Packaging Info.	F64T12D 30/CS 1/SKU
Actual Length (in)	62.000
Actual Length (mm)	1574.80
Average Rated Life (hr)	12000
Base	Single Pin
Bulb	T12
Color Rendering Index (CRI)	76
Color Temperature/CCT (K)	6500
Diameter (in)	1.593
Diameter (mm)	40.46
Initial Lumens at 25C	3300
Mean Lumens at 25C	2904
Mean Lumens at 35C	2904
Nominal Length (in)	64.000
Nominal Length (mm)	1625.60
Nominal Wattage (W)	52.00



Footnotes

- Approximate initial lumens after 100 hours operation.
- The life ratings of fluorescent lamps are based on 3 hr. operating cycles under specified conditions and with ballast meeting ANSI specifications. If operating cycle is increased, there will be a corresponding increase in the average hours life.
- Minimum starting temperature is a function of the ballast; consult the ballast manufacturer.
- Average life rating at 12 hours operation per start is 18,000 hours.