



Product Number: 27259

Order Abbreviation: F72T12/D

General Description: 55W, 72" MOL, T12 instant start Slimline fluorescent lamp, Daylight phosphor, 6500K color temperature, 76 CRI

Product Information

Abbrev. With Packaging Info.	F72T12D 15/CS 1/SKU
Actual Length (in)	70.000
Actual Length (mm)	1778.00
Average Rated Life (hr)	12000
Base	Single Pin
Bulb	T12
Color Rendering Index (CRI)	76
Color Temperature/CCT (K)	6500
Diameter (in)	1.593
Diameter (mm)	40.46
Industry Standards	ANSI C78.81 - 2001
Initial Lumens at 25C	3800
Mean Lumens at 25C	3432
Mean Lumens at 35C	3432
Nominal Length (in)	72.000
Nominal Length (mm)	1828.80
Nominal Voltage (V)	120.00
Nominal Wattage (W)	55.00



Footnotes

- Approximate initial lumens after 100 hours operation.
- The life ratings of fluorescent lamps are based on 3 hr. operating cycles under specified conditions and with ballast meeting ANSI specifications. If operating cycle is increased, there will be a corresponding increase in the average hours life.
- Minimum starting temperature is a function of the ballast; consult the ballast manufacturer.
- Average life rating at 12 hours operation per start is 18,000 hours.