



Product Number: 58678

Order Abbreviation: 50T4Q/CL/AX/24V

General Description: Tungsten Halogen Quartz Bi-Pin STANDARD Low Pressure Clear Finish UV-Filter With Axial Filament GY6.35 Bi-Pin Base 50Watt 24V 2000Hr Lamp Life

Product Information

Abbrev. With Packaging Info.	50T4QCLAX24V 24V 40/CS 1/SKU
Approx. Lumens	900
Average Rated Life (hr)	2000
Base	GY6.35 Bipin
Bulb	T12
Centerbeam Candlepower (cp)	655
Class	G (GAS)
Color Rendering Index (CRI)	100
Color Temperature/CCT (K)	3000
Diameter (in)	0.472
Diameter (mm)	12.00
Ecologic	YES
Family Brand Name	STANDARD Bi-Pin
Filament	CC-8
Lamp Finish	Clear
Light Center Length - LCL (in)	24
Light Center Length - LCL (mm)	28.575
Maximum Overall Length - MOL (in)	1.750
Maximum Overall Length - MOL (mm)	44.45
Nominal Voltage (V)	24.00
Nominal Wattage (W)	50.00

Footnotes

- A protective shield must be used external to the lamp.
- Standard Clear - 24V - UV Filter Quartz - Not suitable for use in open fixtures.