



**Product Number:** 67584

**Order Abbreviation:** LU400/SBY

**General Description:** 400W LUMALUX STANDBY high pressure sodium HID lamp, instant restrike, 40,000hrs avg rated life, E39 based, ET18 bulb, universal burn, clear

### Product Information

Abbrev. With Packaging Info.	LU400SBY 20/CS 1/SKU
ANSI Code	S51
ANSI Code 2	S51
Approx. Lumens (initial - horizontal)	50000
Approx. Lumens (initial - vertical)	50000
Approx. Lumens (mean - horizontal)	40000
Approx. Lumens (mean - vertical)	40000
Arc Length (in)	3.33
Arc Length (mm)	84.6
Average Rated Life - Horizontal (hr)	40000
Average Rated Life - (hr)	40000
Average Rated Life - Vertical (hr)	40000
Avg Rated Life (hrs)	40000
Base	E39 Mogul
Bulb	ET18
Color Rendering Index (CRI)	22
Color Temperature/CCT (K)	2100
Diameter (in)	2.244
Diameter (mm)	57.00
Family Brand Name	Lumalux® Standby
Fixture Requirement	O
Hot Restrike Time (min)	INSTANT
Lamp Finish	Clear
Light Center Length - LCL (in)	5.75
Light Center Length - LCL (mm)	146
Maximum Base Temperature - Fahrenheit	482
Maximum Base Temperature - Celsius	250
Maximum Bulb Temperature - Fahrenheit	752
Maximum Bulb Temperature - Celsius	400
Maximum Overall Length - MOL (in)	9.75
Maximum Overall Length - MOL (mm)	248
Nominal Voltage (V)	100.00
Nominal Wattage (W)	400.00
Operating Position	Universal

Warm-up Time (min)

3-4 MINUTES

**Footnotes**

- Use with 4000V pulse rated sockets only.
- Standby feature not guaranteed beyond 24,000 operating hours.