



**Product Number:** 67500

**Order Abbreviation:** LU35/MED

**General Description:** 35W LUMALUX high pressure sodium HID lamp, E26 based, E17 bulb, universal burn, clear, 1900K

### Product Information

|                                       |                     |
|---------------------------------------|---------------------|
| Abbrev. With Packaging Info.          | LU35MED 20/CS 1/SKU |
| ANSI Code                             | S76                 |
| ANSI Code 2                           | S76                 |
| Approx. Lumens (initial - horizontal) | 2250                |
| Approx. Lumens (initial - vertical)   | 2250                |
| Approx. Lumens (mean - horizontal)    | 2050                |
| Approx. Lumens (mean - vertical)      | 2050                |
| Arc Length (in)                       | 0.89                |
| Arc Length (mm)                       | 22.5                |
| Average Rated Life - Horizontal (hr)  | 16000               |
| Average Rated Life - (hr)             | 16000               |
| Avg Rated Life (hrs)                  | 16000+              |
| Base                                  | E26 Medium          |
| Bulb                                  | E17                 |
| Color Rendering Index (CRI)           | 22                  |
| Color Temperature/CCT (K)             | 1900                |
| Diameter (in)                         | 2.126               |
| Diameter (mm)                         | 54.00               |
| Family Brand Name                     | Lumalux®            |
| Fixture Requirement                   | O                   |
| Hot Restrike Time (min)               | 1 MIN               |
| Lamp Finish                           | Clear               |
| Light Center Length - LCL (in)        | 3.42                |
| Light Center Length - LCL (mm)        | 87                  |
| Maximum Base Temperature - Fahrenheit | 410                 |
| Maximum Base Temperature - Celsius    | 210                 |
| Maximum Bulb Temperature - Fahrenheit | 725                 |
| Maximum Bulb Temperature - Celsius    | 385                 |
| Maximum Overall Length - MOL (in)     | 5.43                |
| Maximum Overall Length - MOL (mm)     | 138                 |
| Nominal Voltage (V)                   | 52.00               |
| Nominal Wattage (W)                   | 35.00               |
| Operating Position                    | Universal           |
| Warm-up Time (min)                    | 3-4 MINUTES         |

**Footnotes**

- Use with 4000V pulse rated sockets only.
- Mean lumens measured at 50% of average rated life