



Product Number: 64737

Order Abbreviation: MSP360/SS/BU-ONLY

General Description: 360W METALARC PRO-TECH SUPERSAVER energy saving quartz metal halide lamp, high output, position dedicated, EX39 base, BT37 bulb, open fixture rated, clear, base up only, 4000K

Product Information

Abbrev. With Packaging Info.	MSP360SSBUONLY 6/CS 1/SKU
ANSI Code	M165/O
ANSI Code 2	M165/O
Approx. Lumens (initial - vertical)	35000
Approx. Lumens (mean - vertical)	23500
Arc Length (in)	1.5
Arc Length (mm)	38
Average Rated Life - Vertical (hr)	20000
Base	EX39 Exclusionary Mogul
Bulb	BT37
Color Rendering Index (CRI)	65
Color Temperature/CCT (K)	4000
Diameter (in)	4.606
Diameter (mm)	117.00
Family Brand Name	Metalarc® Super Saver
Fixture Requirement	O
Hot Restrike Time (min)	7-12
Lamp Finish	Clear
Light Center Length - LCL (in)	7
Light Center Length - LCL (mm)	178
Maximum Base Temperature - Fahrenheit	410
Maximum Base Temperature - Celsius	210
Maximum Bulb Temperature - Fahrenheit	752
Maximum Bulb Temperature - Celsius	400
Maximum Overall Length - MOL (in)	11.5
Maximum Overall Length - MOL (mm)	292
Nominal Voltage (V)	120.00
Nominal Wattage (W)	360.00
Operating Position	Base up within 15deg only
Warm-up Time (min)	2-4

Footnotes

- Operates at 360 watts on 400w M59 ballast or a M165 ballast.

- O = Lamps classified as O-type, comply with ANSI standard C78.389 for containment testing and may be used in open luminaries. See lamp warning.