

**Product Number:** 23487

**Order Abbreviation:** F30T12/CW/RS/UPC

**General Description:** 30W, T12 rapid start fluorescent lamp, Cool White phosphor, 4200K color temperature, 60 CRI, UPC code

**\* Full Case Required**

#### Product Information

Abbrev. With Packaging Info.	F30T12CWRSUPC 30/CS 1/SKU
Actual Length (in)	35.780
Actual Length (mm)	908.81
Average Rated Life (hr)	18000
Base	Medium Bipin
Bulb	T12
Color Rendering Index (CRI)	60
Color Temperature/CCT (K)	4200
Diameter (in)	1.591
Diameter (mm)	40.40
Industry Standards	ANSI C78.81 - 2001
Initial Lumens at 25C	2200
Mean Lumens at 25C	1870
Nominal Length (in)	36.000
Nominal Length (mm)	914.40
Nominal Wattage (W)	30.00

#### Footnotes

- Average rated life is measured at 3 hours per start on 2-lamp, rapid start magnetic ballasts per IES recommended practice. Lamp life on single-lamp rapid start ballasts may be reduced.
- Approximate initial lumens after 100 hours operation.
- The life ratings of fluorescent lamps are based on 3 hr. operating cycles under specified conditions and with ballast meeting ANSI specifications. If operating cycle is increased, there will be a corresponding increase in the average hours life.
- Minimum starting temperature is a function of the ballast; consult the ballast manufacturer.