



Catalog Home

**Product Datasheet**



**ANDERSON FARGO**

**VAUS349349 -- Minimum Tension Splice**



Minimum tension aluminum splice for copper, AAC and ACSR

**Product Specifications**

<p><b>Splice Type</b></p>	 <p><b>VERSAtile™</b> Compression Splices (For use with Die type and VersaCrimp tools)</p>
<p><b>Versatile Compression Series</b></p>	 <p><b>VACS Series</b> Compression Splice VERSAtile™ Minimum Tension Aluminum or Copper Conductor</p>
<p><b>PDF Catalog Page</b></p>	<p><a href="#">Click HERE to view the web page.</a></p>
<p><b>Conventional Tooling Minimum Conductor - End A</b></p>	<p>0.629 in</p>
<p><b>Conventional Tooling Maximum Conductor - End A</b></p>	<p>0.684 in</p>
<p><b>Conventional Tooling Minimum Conductor - End B</b></p>	<p>0.629 in</p>
<p><b>Conventional Tooling Maximum Conductor - End B</b></p>	<p>0.684 in</p>
<p><b>VersaCrimp Tooling Minimum Conductor - End A</b></p>	<p>0.328 in</p>
<p><b>VersaCrimp Tooling Maximum Conductor - End A</b></p>	<p>0.684 in</p>
<p><b>VersaCrimp Tooling Minimum Conductor - End B</b></p>	<p>0.328 in</p>
<p><b>VersaCrimp Tooling Maximum Conductor - End B</b></p>	<p>0.684 in</p>
<p><b>Material</b></p>	<p>Aluminum</p>
<p><b>Conventional Tooling Range End A</b></p>	<p>300-350 Str. &amp; 336.4 18/1 ACSR-350-400 Comp.</p>
<p><b>Conventional Tooling Range End B</b></p>	<p>300-350 Str. &amp; 336.4 18/1 ACSR-350-400 Comp.</p>

<b>VersaCrimp Conductor Minimum - End A</b>	.328 in
<b>VersaCrimp Conductor Maximum - End A</b>	.684 in
<b>VersaCrimp Conductor Range End A</b>	#1-350 Str. & #1-336.4 18/1 ACSR
<b>VersaCrimp Conductor Minimum - End B</b>	.328 in
<b>VersaCrimp Conductor Maximum - End B</b>	.684 in
<b>VersaCrimp Conductor Range End B</b>	#1-350 Str. & #1-336.4 18/1 ACSR
<b>Outside Diameter</b>	0.906 in
<b>Dimension D</b>	1.88 in (48 mm)
<b>Dimension L</b>	4.00 in (102 mm mm)
<b>Length before Compression</b>	4.00 in (102 mm)
<b>Compression Method</b>	VersaCrimp or Conventional Die Tooling
<b>Die Size</b>	840
<b>Cover Available</b>	No
<b>Color Code</b>	None/None
<b>Material Type</b>	Non-Standard
<b>UPC Code</b>	09635933522
<b>Standard Package</b>	25
<b>Standard Package Unit</b>	Each
<b>Min Order Qty</b>	25
<b>Weight / Ea.</b>	0.196 lbs

### Notes

For use with either VersaCrimp or conventional tooling (not for copper to copper connections) factory loaded with non-petroleum sealant.

### Features

Entire VAUS series installs with only 4 common die sizes.

### Compressed Product Number

VAUS349349

[Catalog Home](#)



[Warranty Info](#) | [Trademarks](#) | [Terms of Use](#)

*All contents Copyright © 2007 Hubbell Power Systems, Inc. All rights reserved.*

NOTE: Because Hubbell has a policy of continuous product improvement, we reserve the right to change design and specifications without notice.