Product data sheet Characteristics

EE75S3H TRFMR DRY 1HP 75KVA 240X480V-120/240V

Product availability: Stock - Normally stocked in distribution facility





Price*: 9128.00 USD



Main

Product or component type	Energy Efficient Transformer	
Box number	21D	
NEMA degree of protection	NEMA 2	
Insulation temperature	428 °F (220 °C)	
Phase	1 phase	
Primary voltage	240 x 480 V	
Rated power in VA	75 kVA	
Secondary voltage	120/240 V	
Number of tap-offs	6 2.5 % 2+ 4-	
Temperature rise	150 °C	
Material	Aluminium	

Ordering and shipping details

Category	16284 - 1 PH EE/TP1 LVGP XFMR	
Discount Schedule	PE2E	
GTIN	00785901629665	
Nbr. of units in pkg.	1	
Package weight(Lbs)	647	
Returnability	Υ	
Country of origin	MX	

Offer Sustainability

Sustainable offer status	Green Premium product	nenta
RoHS (date code: YYWW)	Compliant - since 1431 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	This s
REACh	Reference not containing SVHC above the threshold	

Reference not containing SVHC above the threshold

Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations
Contractual warranty	
Warranty period	18 months